

Brady Collapsible Gate Valve Lockouts

Design

- Made of rugged injection-molded acrylonitrile butadiene styrene
- Patent-pending design includes a knock-out center that accommodates OS&Y or "rising stem" valves
- These gate valve lockout covers come in 3 sizes, ranging to cover hand wheels of 3" to 18" in diameter
- Covers fold for easier storage, carrying & application
- Accept locks with shackles up to 3/8" in diameter, and are supplied with danger labels in English, Spanish and French

Material

- Housing: Acrylonitrile butadiene styrene
- Rivet, Washers: Copper, Stainless Steel
- Housing Color: Red (PMS 1805C)
- UL Rating: UL 94 – HB (Plastic Components Only) **Temperature Range**
- Acrylonitrile butadiene styrene : -40° to 100°C (-40° to 212°F)

Chemical °C Chemical °C Chemical Resistance

All approved chemicals listed are based on the Lubrication oil: gear oil manufactures specified chemical resistance chart for plastic
< 120 Water (including seawater),

chlorinated (<0,5 mg/l)⁸⁰

material only. **Dimensions**

Petroleum 25 Lubricating oil: HD engine oils, Water (including seawater) 25 hydraulic oils, transformer oils < 120 **CGV-7 CGV-13**

CGV-18

A 9.03" 14.76" 19.70"

(229.4mm) (374.9mm) (500.4 mm)

B 3.10" 3.98" 3.98"

(78.7mm) (101.1mm) (101.1mm)

C 2.44" 4.11" 5.00"

(62.0mm) (104.5mm) (127.0mm)

D .38" .38" .38"

(9.7mm) (9.7mm) (9.7mm)

E 1.75" 2.90" 2.90"

(44.5mm) (73.7mm) (73.7mm)

F 5.22" 8.20" 10.66"

(132.7mm) (208.2mm) (270.8mm)

G 7.44" 13.63" 18.61"

(189.0mm) (346.2mm) (472.7mm)

Y4278919

Warrant

y

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information. Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods

performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, expressed or implied, and assumes no liability in connection with the use of this information.

MSDS Information

1. HAZARDS IDENTIFICATION

This product is NOT DANGEROUS and contains no hazardous ingredients. **2. FIRST AID MEASURES/HEALTH INFORMATION /PROTECTION**

Eye Contact: Flush with water for at least 20 minutes. Seek medical attention if irritation persists Ingestion: Seek medical attention if a significant amount is swallowed Inhalation: Remove person to fresh air. Assist in breathing if necessary. Seek medical attention. Skin Contact: Not applicable, product is inert, except if product is melted use gloves. For hot melted product, immerse in or flush affected area

with water to dissipate heat, then obtain medical attention. Exposure Limits: None Threshold Limits None Personal Protection: None (ambient conditions) NPCA-HMIS Rating: Health: 0; Flammability: 1; Reactivity: 0 NFPA-704 Rating: Health: 0; Flammability: 1; Reactivity: 0

3. FIRE-FIGHTING MEASURES

- Be cautious of hot melted ABS • Use water spray to cool fire, exposed surfaces, and to protect personnel
- Isolate product from fire • Respiratory and eye protection is required for fire fighting personnel
- Extinguish fire with water spray • Decomposition products under fire conditions: Carbon monoxide, carbon dioxide, hydrogen cyanide.

4. ACCIDENTAL RELEASE MEASURES

Land Recover material and place in suitable container for reuse or for disposal in conformance with local regulations. Water Recover material and place in suitable container for reuse or for disposal in conformance with local regulations.

5. HANDLING AND STORAGE

5.1 Handling 5.2 Storage

No precautions noted-see local regulation if needed Storage pressure: Atmospheric

Storage temperature: Ambient, no direct sunlight

6. EXPOSURE CONTROLS/PERSONAL PROTECTION

6.1 Exposure limit values 6.2 Exposure Controls

None 6.2.1 Occupational Exposure Controls

6.2.1.1 Respiratory Protection: Not applicable 6.2.1.2 Hand Protection: Not applicable 6.2.1.3 Eye Protection: Not applicable 6.2.1.4 Skin Protection: Not applicable 6.2.2 Environmental Exposure Controls: No data available

7. PHYSICAL AND CHEMICAL PROPERTIES

General
Information Other

Information

8. STABILITY AND REACTIVITY

8.1 Conditions to Avoid

Higher Temperatures and direct sunlight Highly stable, but temperatures over 195 F may cause degradation

8.2 Materials to Avoid

No data available

8.3 Hazardous Decomposition Products

Under fire and oxygen-lean conditions may cause monoxide and irritating smoke

Y427891

9

pg 4 of 4

MSDS Information (continued)

9. ECOLOGICAL INFORMATION

9.1 Ecotoxicity No data available 9.2 Mobility No data available 9.3 Persistence and Degradability No data available 9.4 Bioaccumulative Potential No data available 9.5 Other Adverse Effects No data available

10. DISPOSAL CONSIDERATIONS

None of the materials in this product are Recyclable, dispose of all materials in accordance with an applicable federal, state, and local law.

11. TRANSPORT INFORMATION

No data available

12. OTHER INFORMATION

No data available

Catalog Numbers

2"- 7" (50.8mm-

177.8) 148648 7"-13" 330.2mm) (177.8-
148647

13"-18" (330.2mm -

457.2mm) 148646

Y4278919